



THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

December 15, 2004

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE.


APPLICATION NUMBER: 10/713,874

FILING DATE: November 14, 2003

RELATED PCT APPLICATION NUMBER: PCT/US04/36649

Certified by




Jon W Dudas

Acting Under Secretary of Commerce
for Intellectual Property
and Acting Director of the U.S.
Patent and Trademark Office

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. 30682-5

First Inventor Jerome LEGERTON et al.

Title CONTACT LENS

Express Mail Label No. EV292297234US

10270 US PTO
10713874
111403

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO:

Mail Stop Patent Application
Commissioner for Patents
P.O. Box 1450
Alexandria VA 22313-1450

1. ☒ Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
2. ☒ Applicant claims small entity status.
See 37 CFR 1.27.
3. ☒ Specification [Total Pages 27]
(preferred arrangement set forth below)
 - Descriptive title of the invention
 - Cross Reference to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to sequence listing, a table, or a computer program listing appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
4. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 3]
5. Oath or Declaration [Total Sheets 3]
 - a. ☒ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 CFR 1.63(d))
(for continuation/divisional with Box 18 completed)
 - i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s)
name in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
6. ☐ Application Data Sheet. See 37 CFR 1.76

7. ☐ CD-ROM or CD-R in duplicate, large table or Computer Program (Appendix)
8. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
 - a. ☐ Computer Readable Form (CRF)
 - b. Specification Sequence Listing on:
 - i. ☐ CD-ROM or CD-R (2 copies); or
 - ii. ☐ Paper
 - c. ☐ Statements verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

9. ☐ Assignment Papers (cover sheet & document(s))
10. ☐ 37 CFR 3.73(b) Statement ☒ Power of Attorney
(when there is an assignee)
11. ☐ English Translation Document (if applicable)
12. ☒ Information Disclosure Statement & PTO/SB/08 (8 p.) ☐ Copies of IDS Citations
13. ☐ Preliminary Amendment
14. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
15. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
16. ☐ Nonpublication Request under 35 U.S.C. 122
(b)(2)(B)(i). Applicant must attach form PTO/SB/35 or its equivalent.
17. ☒ Other: CERTIFICATE OF EXPRESS MAILING (1 pg.)
Check # 147372 (\$581.00)

18. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in the first sentence of the specification following the title, or in an Application Data Sheet under 37 CFR 1.76:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.:

Prior application information:

Examiner


Art Unit:

For CONTINUATION OF DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 5b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

19. CORRESPONDENCE ADDRESS

☐ Customer Number: OR ☒ Correspondence address below

Name	Peter R. Martinez, Esq.				
Address	LUCE, FORWARD, HAMILTON & SCRIPPS LLP				
	11988 El Camino Real, Suite 200				
City	San Diego	State	CA	Zip Code	92130
Country	U.S.A.	Telephone	858-720-6300	Fax	858-720-6306

Name (Print/Type)	Peter R. Martinez	Registration No. (Attorney/Agent)	42,845
Signature		Date	November 14, 2003

This collection of information is required by 37 CFR 1.53(b). The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Mail Stop Patent Application, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

The PTO did ~~not~~ receive the following
Listed item(s) A-check for
\$ 581.00

PTO/SB/17 (10-03)
Approved for use through 07/31/2006. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

FEE TRANSMITTAL for FY 2004

Effective 10/01/2003. Patent fees are subject to annual revision.

☒ Applicant claims small entity status. See 37 CFR 1.27

TOTAL AMOUNT OF PAYMENT (\$ 687.00)

Complete if Known

Application Number	To be assigned
Filing Date	November 14, 2003
First Named Inventor	Jerome LEGERTON et al.
Examiner Name	To be assigned
Art Unit	To be assigned
Attorney Docket No.	30682-5

METHOD OF PAYMENT (check all that apply)

☒ Check ☐ Credit card ☐ Money Order ☐ Other ☐ None

☒ Deposit Account:

Deposit Account Number: 50-2298
Deposit Account Name: LUCE FORWARD & SCRIPPS, LLP

The Director is authorized to: (check all that apply)

☐ Charge fee(s) indicated below ☐ Credit any overpayments

☒ Charge any fee(s) due during the pendency of this application

☐ Charge fee(s) indicated below, except for the filing fee to the above-identified deposit account.

FEE CALCULATION

1. BASIC FILING FEE

Large Entity Fee Code (\$)	Small Entity Fee Code (\$)	Fee Description	Fee Paid
1001 770	2001 385	Utility filing fee	385
1002 340	2002 170	Design filing fee	
1003 530	2003 265	Plant filing fee	
1004 770	2004 385	Reissue filing fee	
1005 160	2005 80	Provisional filing fee	
SUBTOTAL (1)			(\$ 385)

2. EXTRA CLAIM FEES FOR UTILITY AND REISSUE

Total Claims 44 - 20** = 24 x 9 = 216
Independent Claims 5 - 3** = 2 x 43 = 86
Multiple Dependent =

Large Entity Fee Code (\$)	Small Entity Fee Code (\$)	Fee Description
1202 18	2202 9	Claims in excess of 20
1201 86	2201 43	Independent claims in excess of 3
1203 290	2203 145	Multiple dependent claim, if not paid
1204 86	2204 43	** Reissue independent claims over original patent
1205 18	2205 9	** Reissue claims in excess of 20 and over original patent

SUBTOTAL (2) (\$ 302)

**or number previously paid, if greater; For Reissues, see above

FEE CALCULATION (continued)

3. ADDITIONAL FEES

Large Entity - Small Entity

Fee Code (\$)	Fee Code (\$)	Fee Description	Fee Paid
1051 130	2051 65	Surcharge - late filing fee or oath	
1052 50	2052 25	Surcharge - late provisional filing fee or cover sheet	
1053 130	1053 130	Non-English specification	
1812 2,520	1812 2,520	For filing a request for <i>ex parte</i> reexamination	
1804 920*	1804 920*	Requesting publication of SIR prior to Examiner action	
1805 1,840*	1805 1,840*	Requesting publication of SIR after Examiner action	
1251 110	2251 55	Extension for reply within first month	
1252 420	2252 210	Extension for reply within second month	
1253 950	2253 475	Extension for reply within third month	
1254 1,480	2254 740	Extension for reply within fourth month	
1255 2,010	2255 1,005	Extension for reply within fifth month	
1401 330	2401 165	Notice of Appeal	
1402 330	2402 165	Filing a brief in support of an appeal	
1403 290	2403 145	Request for oral hearing	
1451 1,510	1451 1,510	Petition to institute a public use proceeding	
1452 110	2452 55	Petition to revive - unavoidable	
1453 1,330	2453 665	Petition to revive - unintentional	
1501 1,330	2501 665	Utility issue fee (or reissue)	
1502 480	2502 240	Design issue fee	
1503 640	2503 320	Plant issue fee	
1460 130	1460 130	Petitions to the Commissioner	
1807 50	1807 50	Processing fee under 37 CFR 1.17(q)	
1806 180	1806 180	Submission of Information Disclosure Stmt	
8021 40	8021 40	Recording each patent assignment per property (times number of properties)	
1809 770	2809 385	Filing a submission after final rejection (37 CFR 1.129(a))	
1810 770	2810 385	For each additional invention to be examined (37 CFR 1.129(b))	
1801 770	2801 385	Request for Continued Examination (RCE)	
1802 900	1802 900	Request for expedited examination of a design application	


Other fee (specify) _____

*Reduced by Basic Filing Fee Paid

SUBTOTAL (3) (\$)

SUBMITTED BY

(Complete if applicable)

Name (Print/Type)	Peter R. Martinez	Registration No. (Attorney/Agent)	42,845	Telephone	858-720-6300
Signature		Date	November 14, 2003		

WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

This collection of information is required by 37 CFR 1.17 and 1.27. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2

Atty. Docket No.: 30682-5

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

NON-PROVISIONAL UTILITY PATENT APPLICATION:

CONTACT LENS

Inventors: Jerome Legerton
Barry Chen

LUCE FORWARD HAMILTON & SCRIPPS LLP
11988 El Camino Real, Suite 200
San Diego, California 92130
(858) 720-6300

CONTACT LENS

5

Field Of The Invention

The present invention generally relates to contact lenses. More particularly, the invention concerns contact lens construction features and methods of fitting and prescribing a contact lens.

10

Background Of The Invention

15

Vision correction is on the verge of a revolution. New technologies to measure the aberrations or distortions in the optics of the eye will soon be available to the public. These new wavefront measurement techniques such as Shack-Hartmann wavefront sensing or Talbot Interferometry can precisely measure the eye's aberrations so that vision may be corrected up to 20/10. Wavefront sensing is the method for rapidly, and very accurately, assessing the aberrations in an individual's eye to create a customized prescription for correction.

20

However, once the eye's aberrations have been measured, either by conventional methods or by wavefront sensing, these measurements must then be transferred into a vision correction system, such as eye surgery, spectacles, or contact lenses. Recent advances in laser refractive surgery techniques such as LASIK and photorefractive keratectomy, as well as improvements in spectacle lens manufacturing now enable the creation of highly accurate corrective prescriptions for individuals.

However, this is not the case with contact lenses. Popular soft contact lenses cannot achieve the same result as spectacles or laser refractive surgery because of dimensional variations in contact lens fabrication. Hard contact lenses, which may provide the platform to achieve the results of spectacles, are not as comfortable as soft contacts and generally lack the necessary positional stability on the eye.

Therefore, there exists a need for a contact lens that aid in the generation of an accurate corrective prescription and that can provide a stable platform for the prescription.

Summary Of The Invention

A contact lens is provided. One embodiment of the present invention provides a method for fitting and prescribing a contact lens. Another embodiment of the present invention comprises a contact lens construction that provides a stable corrective prescription platform. Yet another embodiment comprises a contact lens that is constructed to accommodate ectasia associated with keratoconus.

For example, in one embodiment, a contact lens constructed according to the present invention comprises a central portion including an optical zone, and a peripheral portion surrounding the central portion. The peripheral portion has a first thickness, and it includes at least two areas of unequal size, with each area having a thickness less than the first thickness. Alternatively, one area may have a thickness less than the first thickness, and the second area may have a thickness greater than the first thickness. This contact lens construction provides a platform that resists rotation, thereby maintaining the contact lens in the desired rotational orientation on an eye.

These and other features and advantages of the present invention will be appreciated from review of the following detailed description of the invention, along with the accompanying figures in which like reference numerals refer to like parts throughout.

Brief Description Of The Drawings

FIG. 1 is a plan view of a contact lens constructed according to one embodiment of the present invention;

FIG. 2 is a sectional view taken along cutting plane 2 -- 2 of FIG. 1;

FIG. 3 is a plan view of a contact lens constructed according to a second embodiment of the present invention;

FIG. 4 is a plan view of a contact lens constructed according to yet another embodiment of the present invention;

FIG. 5 is a sectional view taken along cutting plane 5 -- 5 of FIG. 4;

FIG. 6A is a plan view of a contact lens constructed according to yet another embodiment of the present invention;

FIG. 6B is a plan view of a contact lens constructed according to a further embodiment of the present invention; and

FIG. 7 is a magnified view of a section of a contact lens constructed to another embodiment of the present invention.

It will be recognized that some or all of the Figures are schematic representations for purposes of illustration and do not necessarily depict the actual relative sizes or locations of the elements shown. The Figures are provided for the purpose of illustrating one or more

embodiments of the invention with the explicit understanding that they will not be used to limit the scope or the meaning of the claims.

Detailed Description Of The Invention

5 In the following paragraphs, the present invention will be described in detail by way of example with reference to the attached drawings. Throughout this description, the preferred embodiment and examples shown should be considered as exemplars, rather than as limitations on the present invention. As used herein, the "present invention" refers to any one of the embodiments of the invention described herein, and any equivalents. Furthermore, reference to
10 various feature(s) of the "present invention" throughout this document does not mean that all claimed embodiments or methods must include the referenced feature(s).

 The present invention relates to contact lenses, and includes both homogenous lenses, and hybrid hard-soft contact lenses. In one embodiment of the present invention, a contact lens includes areas, or regions of unequal size that are thinner than adjacent regions of the contact
15 lens. One feature of this embodiment is that the contact lens provides rotational stability and therefore maintains a correct rotational position on a wearer's eye.

 In another embodiment of the present invention, a contact lens may include a recess that is sized to accommodate a keratoconus or other type of ectasia. Specifically, an ectasia is a bump or raised feature on an eye. The contact lens constructed according to the present
20 invention would include a recess sized to accommodate this bump, therefore allowing individuals with keratoconus to comfortably wear a contact lens.

 Another embodiment of the present invention includes different marks that are placed on the lens. These marks are used by an optometrist or other contact lens provider to determine if

the lens is correctly positioned on the eye. Specifically, the rotational as well as translational position of the lens on the eye can be determined using the marks constructed according to the present invention.

Contact lenses that contain the features of the present invention may be “hard” lenses, “soft” lenses, or hybrid hard-soft contact lenses that are comprised of a substantially rigid central portion and a softer, flexible outer portion.

Referring to FIG. 1, a contact lens 10 is illustrated. The contact lens 10 includes a central portion 15 and a peripheral portion 20. The central portion 15 has a diameter that is at least as large as the optical region of an eye lens. That is, the central portion 15 has an outer diameter that is at least as large as the outer diameter of an iris of an individual’s eye. Thus, the central portion 15 includes the optical area, or zone that provides corrective vision to the wearer. This central portion 15 may have a diameter that may range between about 4.0 mm to about 12.0 mm. The peripheral portion 20 may have an outer diameter that may range between about 10.0 mm to about 18.0 mm.

The peripheral portion 20 includes a first region or area 25 and a second region or area 30. As shown in FIG. 1, these regions 25 and 30 are asymmetrical, or unequal in area. Illustrated in FIG. 2, the first area 25 and second area 30 comprise recesses on the peripheral portion 20 that are thinner than adjacent areas on the peripheral portion 20. In this embodiment, because the first region 25 has less mass than the second region 30, the contact lens 10 will orient itself with the second region 30 aligned with the earth’s gravity. That is, because the top half 22 of the contact lens 10 has less mass than the bottom half 24 of the contact lens, the contact lens 10 will orient itself with the greater mass aligned with the earth’s gravitational pull.

This will maintain the rotational orientation of the contact lens in the desired position, thereby providing a stable platform for a corrective prescription.

An alternative embodiment may also have regions 25 and 30 that are asymmetrical, or unequal in area. However, in this embodiment, the first area 25 may include a recess, but the second area 30 may comprise a bump. That is, the second area 30 may have a thickness greater than an adjacent peripheral portion 20 thickness. Similar to the first embodiment, because the first region 25 has less mass than the second region 30, the contact lens 10 will orient itself with the second region 30 aligned with the earth's gravity. That is, because the top half 22 of the contact lens 10 has less mass than the bottom half 24 of the contact lens, the contact lens 10 will orient itself with the greater mass aligned with the earth's gravitational pull.

Alternatively, the first and second regions 25, 30 may be positioned in any area of the peripheral portion 20, and any relationship relative to each other. In this embodiment, the regions 25, 30 may work in conjunction with eyelid forces that may vary between the upper and lower eyelids. In this embodiment, the dominant force on the contact lens 10 may be the eyelid forces rather than gravity.

Again referring to FIG. 1, the shape, and orientation of the first region 25 and second region 30 may vary, and include any number of suitable configurations. For example, as shown in FIG. 1, the general shape of one embodiment of each region 25 and 30 will accommodate the outer diameter of the contact lens 10. Specifically, the medial most portion of each region 25, 30 may be described by the radial distance from the geometric center of the contact lens 10. Similarly, in this embodiment, the peripheral-most portion of each region 25, 30 may be described by the radial distance from the geometric center of the contact lens 10. Other constructions may define a width of each region 25, 30 by an angle subtended from the

geometric center of the contact lens 10. Regarding the depth of the recess that forms each region 25, 30, the depth may be described by the departure from a sphere comprising the posterior portion of the contact lens 10. The depth of each region 25, 30 may also vary, to achieve the desired lens stability requirements.

5 In addition, in alternative embodiment contact lenses 10, the location of the first region 25 and second region 30 may vary. That is, the radial position of each region 25, 30 may vary to suit individual lens requirements. Moreover, as shown in FIG. 2, each region 25, 30 is located on the anterior, or front surface of the contact lens 10. Alternatively, each region 25, 30 may be located on the posterior, or rear (eye facing) surface.

10 Referring now to FIG. 3, another embodiment of the contact lens 10 is illustrated. This embodiment includes a central portion 15, a peripheral portion 20, and a circumferential mark 35 as well as a radial mark 40. One feature of the present invention involves a method or system for fitting and obtaining a corrective prescription for a contact lens. In this embodiment, an optometrist or other contact lens provider employs one or more "fitting" contact lenses. The
15 provider places one, or two, of these "fitting" contact lenses on an individual as part of the process to obtain a corrective prescription.

Of interest to an optometrist during the process of obtaining a corrective prescription, is the relative relationship between the patient's eye lens and the center of the patient's eye pupil or the visual axis of the patient's eye. Often, an individual's eye lens is not aligned with the center
20 of their pupil or not aligned with the visual axis of their eye. This misalignment is known as registration disparity or registration error. To obtain a very accurate corrective prescription, it is generally desirable to know this registration error so that the corrective prescription can be placed in the correct location on the contact lens 10.

In one method of the present invention, a fitting contact lens 10 is placed on the eye, and the marks 35, 40 are employed to aid in determining the registration error. The residual optical errors are also determined, and a final contact lens prescription is obtained.

In an embodiment of the present invention a contact lens 10 will be manufactured to include quarter-wavelength customization in order to correct for the higher order refractive aberrations that limit one's ability to see better than 20/20. Other embodiments of the present invention will correct normal ametropic errors (myopia, hyperopia and astigmatism) to a higher degree of visual performance than conventional contact lenses. Another embodiment of the present invention will correct for the wavefront-guided higher order aberrations and will create a new contact lens category, providing "super vision" for those whose visual requirements demand better than 20/20 acuity. Yet another embodiment of the present invention will correct for presbyopia, the gradually increasing inability to focus at close distances that usually begins after age 40. Other embodiments of the present invention may include contact lenses that incorporate several, or all of the above-described features.

An accurate prescription process is desirable when producing contact lenses 10 that include some, or all of the above capabilities. The present invention contemplates several methods of prescribing and fitting a contact lens 10. One method relates to non-rotating lenses for correcting high-order aberrations that include methods of placing the coordinates of the aberration measurement over the ~~coordinates of the pupil~~. Another comprises methods of placing a multifocal over the coordinates of the pupil and customizing the design of the multifocal with measurements of high order aberrations and pupil size.

Again referring to FIG. 3, the circumferential mark 35 and the radial mark 40 may be placed on either the anterior or posterior contact lens 10 surfaces or within the matrix of either

the central portion 15, or in the peripheral portion 20 of the contact lens 10. In one embodiment, the circumferential mark 35 and the radial mark 40 are both located on the peripheral portion 20 of the contact lens 10. Other types of marks may be employed by the present invention. They include: a circumferential mark; a radial mark; at least three marks concentric to a contact lens 10 center and a radial mark; a circumferential mark and a radial mark; a grooved mark; and an elevated mark. The grooved mark may comprise a recess, or indentation on the surface of the contact lens 10, and the elevated mark may comprise a bump, or raised area on the surface of the contact lens 10. The marks described above may be visible to the eye under ambient light, or they may be visible by employing infrared light. In addition, the mark or marks may be made visible by varying of the index of refraction of the contact lens 10 material.

In a preferred embodiment, a contact lens 10 includes two marks that intersect. That is, the mark comprises a first line that intersects a second line. For example, as shown in FIG. 3, the circumferential mark 35 and the radial mark 40 intersect each other. In other embodiments, the mark may include an alphabet letter, such as a "L" or a "R", as shown in FIGS. 6A-B. A discernable L and R on a corresponding left and right contact lens 10 would assist a wearer in placing the correct contact lens 10 on the correct eye. In addition, the marks would aid the individual in correctly orienting the contact lens 10 on the eye.

As shown in FIG. 3, one feature of this embodiment of the present invention, is that the circumferential mark 35 and the radial mark 40 aid in determining the eye lens rotational and translational registration error. That is, the circumferential mark 35 and the radial mark 40 facilitate the lens provider in determining an eye lens rotational and translational registration error relative to a center of an eye pupil or to an eye visual axis. In practice, a "fitting" contact lens 10 containing one or more marks as described above, is placed on an individual's eye. The

marks are detectable by a corneal topographer, an aberrometer, a video keratography system, or other devices employed by an optometrist or contact lens provider. By using the marks as a reference, the registration error of the eye can be determined, and a contact lens 10 incorporating a correction for the registration error can be manufactured. That is, the location and orientation of the corrective prescription may be moved on the contact lens 10 based on the registration error information.

For example, a contact lens 10 containing one or more marks as described above is placed on an eye and allowed to equilibrate. The degree of rotational and translational movement is observed by observing the marks. The residual high- and low-order aberrations are measured through the contact lens 10 along with, possibly, the relative coordinates of the lens marks and the pupil margin, limbal margin or other anatomical features. That is, in the preferred embodiment, an instrument having the capability of detecting the contact lens 10 marks and the pupil margin along with the residual high and low order aberrations is used. However, this additional information is not always necessary to obtain a corrective prescription.

An alternative embodiment of the present invention may include infrared-responsive marks, such as one or more registration marks, one or more concentric marks, or other suitable marks, which emit, reflect or are excited by infrared light. For example, some types of wavefront aberrometers employ infrared light, which is generally in the form of a laser. During examination of an eye fitted with a contact lens 10 constructed according to the present invention, the infrared-reflecting marks in the contact lens 10 will be easily visible, enabling simultaneous evaluation of registration error, as well as any aberrations. In one embodiment, indocyan dye is employed, but it will be appreciated that other dyes, powders, or other types of infrared or ultraviolet responsive products may be employed.

Another method of prescribing and fitting a hybrid contact lens employs a set of precision rotating and non-rotating contact lenses 10 having known ocular surface profiles, optical corrections and thickness profiles. In one embodiment, the contact lenses 10 contain one or more circumferential marks 35, radial marks 40 or other types of marks as described above, in the mid-periphery (as shown, in part, in FIG. 3). In this embodiment, a contact lens 10 is selected and applied to the eye and allowed to equilibrate. The coordinates of the marks and the pupil are determined. The aberrations of the lens-eye system are measured. A mathematical model provides analysis of the known thickness profile, the registration error of the coordinates of the contact lens 10 and the pupil, and the residual lens-eye aberrations to derive the computer numerically controlled lathe files for producing a resultant thickness profile for a final contact lens having the same ocular surface profile.

For example, one prescribing and fitting method of the present invention may include the steps of: selecting an initial contact lens 10 to conform to the shape of the underlying cornea; capturing an image of the circumferential mark 35 and/ or the radial mark 40, and the pupil margin; measuring the residual low and high order aberrations of the lens-eye system; performing analysis utilizing the known ocular surface profile of the contact lens 10, the initial lens thickness profile, the registration error, and the residual lens-eye aberration error to determine the resultant files for generating a final corrective prescription contact lens.

Another method of the present invention comprises correcting visual acuity deficiencies in presbyopia by reduction of the residual lens-eye aberrations. The method uses a set of contact lenses 10 having a known ocular surface profile and thickness profile and containing one or more circumferential mark(s) 35 and/or radial mark(s) 40 for the purpose of registration of the final optical correction with the coordinates of the optical system of the eye. The method steps may

include: selecting the initial contact lens 10 to conform to the shape of the underlying cornea; capturing an image of the circumferential marks 35 and the pupil margin; measuring the size of the pupil in photopic, mesopic and/or scotopic illumination; measuring the residual low and high order aberrations of the lens-eye system; and performing analysis utilizing the known ocular surface profile, the initial lens thickness profile, the registration error, the pupil size and the residual lens-eye aberration error to determine prescription information for generating a final contact lens. In one embodiment of this method, the diameter of the near focused optical correction may be in the range of about 1.8 mm to about 4.0 mm.

Another method of the present invention employs a multifocal contact lens 10 and corrects visual acuity deficiencies in presbyopia by reduction of the residual lens-eye aberrations. The method uses a set of multifocal contact lenses 10 having a known ocular surface profile and thickness profile and containing circumferential marks 35, radial marks 40 or other types of marks as described above, for the purpose of registration of the final optical correction with the coordinates of the optical system of the eye. The method steps may include: selecting the initial lens to conform to the shape of the underlying cornea having a multifocal anterior surface; capturing an image of the circumferential marks and the pupil margin; measuring the size of the pupil in photopic, mesopic and/or scotopic illumination; measuring the residual low and high order aberrations of the lens-eye system; and performing analysis utilizing the known ocular surface profile, the initial lens thickness profile, the registration error, the pupil size and the residual lens-eye aberration error to determine prescription information for generating a final multifocal contact lens. In one embodiment of this method, the diameter of the near focused optical correction may be in the range of about 1.8 mm to about 4.0 mm.

Another method of the present invention employs a multifocal contact lens and corrects visual acuity deficiencies in presbyopia by reduction of the residual lens-eye aberrations. This method also incorporates information relating to a light transmittance pattern. The method uses a set of multifocal contact lenses 10 having a known ocular surface profile and thickness profile, light transmittance pattern, and containing one or more circumferential marks 35, radial marks 40 or other types of marks as described above, for the purpose of registration of the final optical correction with the coordinates of the optical system of the eye. The method steps may include: selecting the initial lens to conform to the shape of the underlying cornea having a multifocal anterior surface; capturing an image of the circumferential marks and the pupil margin; measuring the size of the pupil in photopic, mesopic and/or scotopic illumination; measuring the residual low and high order aberrations of the lens-eye system; and performing analysis utilizing the known ocular surface profile, the initial lens thickness profile, the registration error, the light transmittance pattern, the pupil size and the residual lens-eye aberration error to determine prescription information for generating a final multifocal contact lens. In one embodiment of this method, the diameter of the near focused optical correction may be in the range of about 1.8 mm to about 4.0 mm.

The above-described methods of prescribing and/or fitting contact lens 10 may also employ additional method steps or additional devices. For example: the method of determining the difference in the coordinates of the center of the circumferential marks 35 and the pupil margin may incorporate a reticle of a biomicroscope or a camera with subsequent manual or electronic digital image detection. In addition, the method of measuring the residual aberrations of the lens-eye system may incorporate Shack-Hartmann aberrometry, aberrometers utilizing Tscherning technology, laser ray-tracing or Talbot interferometry technology.

Referring again to FIG. 3, and to the feature of the present invention of using marks on a contact lens 10, an optometrist or other contact lens provider wishing to obtain a corrective prescription uses these circumferential marks 35, 40 during the prescription process to obtain information relating to the rotational as well as the translational position of the contact lens 10 on the individual's eye. Other types of contact lens 10 marks may include only a circumferential mark 35, only a radial mark 40, or as shown in FIG. 3, a circumferential mark 35 used in conjunction with a radial mark 40. Other marks may also include at least three radial marks that are concentric to a contact lens center as well as other suitable types of marks.

As shown in the embodiment illustrated in FIG. 3, the contact lens 10 includes a circumferential mark 35 and radial mark 40. The contact lens 10 is placed on an individual's eye and the optometrist can view the individual's eye pupil, lens and visual axis and using the circumferential mark 35 and/or the radial mark 40 determine any registration error in the individual's eye. Specifically, because the optometrist knows the diameter of the circumferential mark 35 he can still determine the necessary information if he only sees part of the circumferential mark 35 and the radial mark 40. This is because the location of the center of the circumferential mark 35 can be determined even if only part of the circumferential mark 35 is viewable because the diameter of the circumferential mark 35 is known.

Referring now to FIG. 4, another feature of the contact lens 10 constructed according to the present invention is illustrated. The contact lens 10 illustrated in FIG. 4 includes a central portion 15, peripheral portion 20 and one or more recessed areas 45. As shown in FIG. 5, the recessed area 45 is located on the posterior or eye-facing surface of the contact lens 10. The recessed area 45 may be of any shape or size to accommodate a bump or ectasia generally resulting from keratoconus. One feature of this contact lens 10 is that the recessed area 45 can

be sized and located on the contact lens 10 so that an individual with keratoconus can wear the contact lens and the recessed area 45 will accommodate the ectasia. This enables individuals suffering from keratoconus to comfortably wear a contact lens 10.

Referring to FIGS. 6A and 6B, another feature of the contact lens 10 is illustrated. As shown in FIG. 6A, a letter "L" is placed on the contact lens and as shown in FIG. 6B, a letter "R" is placed on the contact lens 10. During the fitting of a corrective set of contact lenses 10 the individual wearer can place these lens on the left and right eyes and the practitioner or optometrist can verify the translational and rotational position of the lens by using the "L" and "R" as reference marks. Specifically, the vertical and horizontal components of the "L" can be used as vertical and horizontal indicators to determine rotational and translational position. Similarly, the vertical component of the "R" as well as the horizontal component of the top of the "R" can also be used to verify translational and rotational position. As shown in FIG. 6A-B, an alternative embodiment "L" and "R" may include an extension above the "R" and below the "L" to aide the optometrist in determining rotational and/or translational position.

Specifically, as shown in FIGS. 6A-B, in this embodiment, the top of the R is perpendicular to the vertical side of the R. Similarly, the lines comprising the L are also perpendicular. These perpendicular lines form a small cross, that enables the contact lens provider to determine rotational and translational movement of the contact lens 10 relative to the eye. In addition, the L and R marks may be used by the wearer to assist in placing the lens so the lens is oriented properly in the eye, and that the correct lens is placed in the correct eye.

The contact lens 10 of the present invention may be either a "hard" lens, "soft" lens, or a hybrid hard-soft contact lens that is comprised of a substantially rigid central portion 15 and a softer, flexible peripheral portion 20. Referring to FIG. 7, a portion of a hybrid hard-soft contact

lens 10 is illustrated. Conventional hybrid contact lenses are generally not durable, in part because of the fragile connection between the hard and soft sections of the lens. One feature of the present invention is that a V-shaped coupling configuration is contemplated that securely couples the hard and soft sections of a hybrid contact lens 10.

5 As shown in FIG. 7, the central portion 15 is coupled to the peripheral portion 20 at a V-shaped junction. Alternatively, the V-shape, which is comprised of sides, or legs 75, may be switched so that the apex extends into the central portion 15. Each angle "A" may range between about 95 degrees to about 170 degrees. In a preferred embodiment, angle A ranges between about 110 degrees to about 165 degrees. As illustrated, the interface between the hard,
10 or substantially rigid lens material that comprises the central portion 15, and the soft lens material that comprises the peripheral portion 20 is substantially V-shaped. Put differently, the interface comprises two intersecting planes that meet within the lens. This lens junction configuration provides a safety feature in the unlikely case of lens material separation during wear. Because of the V-shape, the edge of the hard lens material comprising the central portion
15 15 is not "blade" shaped, and thus a sharp edge will not contact the cornea or eyelid, eliminating the risk of cuts, or abrasions.

Thus, it is seen that a contact lens system, method, and article of manufacture is provided. One skilled in the art will appreciate that the present invention can be practiced by other than the above-described embodiments, which are presented in this description for purposes of illustration
20 and not of limitation. The description and examples set forth in this specification and associated drawings only set forth preferred embodiment(s) of the present invention. The specification and drawings are not intended to limit the exclusionary scope of this patent document. It is noted

that various equivalents for the particular embodiments discussed in this description may practice the invention as well.

CLAIMS

What is claimed is:

1. A contact lens comprising:
a central portion including an optical zone;
a peripheral portion surrounding the central portion, the peripheral portion having a first thickness; and
at least two areas of unequal size located on the peripheral portion, with each area having a thickness less than the first thickness.
2. The contact lens of claim 1, wherein the thickness of the at least two zones is unequal.
3. The contact lens of claim 1, wherein the contact lens is a hybrid hard-soft contact lens, with the central portion being substantially rigid, and the peripheral portion being substantially flexible.
4. The contact lens of claim 3, wherein the central portion has a diameter that ranges between about 4.0 millimeters to about 12.0 millimeters, and the peripheral portion has an outer diameter that ranges between about 10.0 millimeters to about 18.0 millimeters.

5. The contact lens of claim 1, wherein the central portion has a diameter that ranges between about 4.0 millimeters to about 12.0 millimeters, and the peripheral portion has an outer diameter that ranges between about 10.0 millimeters to about 18.0 millimeters.
6. The contact lens of claim 1, further including a junction between the central portion and the peripheral portion, with the junction comprising a substantially V-shaped surface.
7. The contact lens of claim 1, wherein an angle comprising the substantially V-shaped surface ranges between about 10 degrees to about 170 degrees.
8. The contact lens of claim 1, wherein the contact lens is constructed to include a prescription obtained from a wavefront aberrometer.
9. The contact lens of claim 1, wherein the contact lens is constructed to include a prescription for presbyopia.
10. The contact lens of claim 1, wherein the contact lens is constructed to include a mark for determining a registration error.
11. The contact lens of claim 10, wherein the mark is selected from a group consisting of: a circumferential mark; a radial mark; at least three marks concentric to a contact lens center and a radial mark; a circumferential mark and a radial mark; a

grooved mark; an elevated mark; and a mark having a index of refraction greater than an index of refraction in an adjacent material.

12. The contact lens of claim 10, wherein the mark is visible with a light selected from a group consisting of: a light having a wavelength ranging from about 700 nanometers to about 400 nanometers; an infrared light; and a ultraviolet light.

13. A contact lens comprising:

a central portion including an optical zone;

a peripheral portion surrounding the central portion, the peripheral portion having a first thickness; and

at least one area located on the central portion, with the area having a thickness less than the first thickness.

14. The contact lens of claim 13, wherein the at least one area is structured to accommodate a keratoconus ectasia.

15. The contact lens of claim 13, wherein the contact lens is a hybrid hard-soft contact lens, with the central portion being substantially rigid, and the peripheral portion being substantially flexible.

16. The contact lens of claim 13, wherein the central portion has a diameter that ranges between about 4.0 millimeters to about 12.0 millimeters, and the peripheral

portion has an outer diameter that ranges between about 10.0 millimeters to about 18.0 millimeters.

17. The contact lens of claim 13, further including a junction between the central portion and the peripheral portion, with the junction comprising a substantially V-shaped surface.

18. The contact lens of claim 13, wherein an angle comprising the substantially V-shaped surface ranges between about 10 degrees to about 170 degrees.

19. The contact lens of claim 13, wherein the contact lens is constructed to include a prescription obtained from a wavefront aberrometer.

20. The contact lens of claim 13, wherein the contact lens is constructed to include a prescription for presbyopia.

21. The contact lens of claim 13, wherein the contact lens is constructed to include a mark for determining a registration error.

22. The contact lens of claim 21, wherein the mark is selected from a group consisting of: a circumferential mark; a radial mark; at least three marks concentric to a contact lens center and a radial mark; a circumferential mark and a radial mark; a

grooved mark; an elevated mark; and a mark having a index of refraction greater than an index of refraction in an adjacent material.

23. A method of obtaining a corrective prescription, the method comprising the steps of:

providing at least one contact lens, the contact lens having at least two areas of unequal size, with each area comprising a recessed region;

placing the contact lens on an eye; and

obtaining a corrective prescription while the contact lens is on the eye.

24. The method of claim 23, wherein the recessed region comprises a contact lens area having a thickness that is less than an adjacent contact lens area thickness.

25. The method of claim 23, wherein the step of obtaining a corrective prescription while the contact lens is on the eye includes the step of:

determining an eye lens rotational and translational registration error relative to a center of an eye pupil or to an eye visual axis.

26. The method of claim 25, wherein the contact lens includes at least one mark for determining the eye lens rotational and translational registration error.

27. The method of claim 26, wherein the mark is selected from a group consisting of: a circumferential mark; a radial mark; at least three marks concentric to the contact lens

center and a radial mark; a circumferential mark and a radial mark; a grooved mark; an elevated mark; and a mark having an index of refraction greater than an index of refraction in an adjacent material.

28. The method of claim 26, wherein the mark is visible with a light selected from a group consisting of: a light having a wavelength ranging from about 700 nanometers to about 400 nanometers; an infrared light; and a ultraviolet light.

29. A contact lens comprising:

a central portion including an optical zone;

a peripheral portion surrounding the central portion, the peripheral portion including a mark comprising a first line that intersects a second line

30. The contact lens of claim 29, wherein the central portion has a diameter that ranges between about 4.0 millimeters to about 12.0 millimeters, and the peripheral portion has an outer diameter that ranges between about 10.0 millimeters to about 18.0 millimeters.

31. The contact lens of claim 29, wherein the mark comprises a cross comprises a first line that intersects a second line.

32. The contact lens of claim 29, further comprising a mark comprising an alphabet letter.

33. The contact lens of claim 32, wherein the alphabet letter is a "L" or a "R".
34. The contact lens of claim 32, wherein the alphabet letter assists a wearer in placing the contact lens so that the contact lens is oriented properly in an eye.
35. The contact lens of claim 29, wherein the mark is used by a contact lens fitter to determine an orientation of the contact lens in an eye and for placement of a corrective optic prescription within the contact lens.
36. The contact lens of claim 29, wherein the contact lens is a hybrid hard-soft contact lens, with the central portion being substantially rigid, and the peripheral portion being substantially flexible.
37. A contact lens comprising:
- a central portion including an optical zone;
 - a peripheral portion surrounding the central portion, the peripheral portion having a first thickness; and
 - at least two areas of unequal size located on the peripheral portion, with a first area having a thickness less than the first thickness, and a second area having a thickness greater than the first thickness.

38. The contact lens of claim 37, wherein the contact lens is a hybrid hard-soft contact lens, with the central portion being substantially rigid, and the peripheral portion being substantially flexible.

39. The contact lens of claim 37, wherein the central portion has a diameter that ranges between about 4.0 millimeters to about 12.0 millimeters, and the peripheral portion has an outer diameter that ranges between about 10.0 millimeters to about 18.0 millimeters.

40. The contact lens of claim 37, wherein the contact lens is constructed to include a prescription obtained from a wavefront aberrometer.

41. The contact lens of claim 37, wherein the contact lens is constructed to include a prescription for presbyopia.

42. The contact lens of claim 37, wherein the contact lens is constructed to include a mark for determining a registration error.

43. The contact lens of claim 42, wherein the mark is selected from a group consisting of: a circumferential mark; a radial mark; at least three marks concentric to a contact lens center and a radial mark; a circumferential mark and a radial mark; a grooved mark; and an elevated mark.

44. The contact lens of claim 42, wherein the mark is visible with a light selected from a group consisting of: a light having a wavelength ranging from about 700 nanometers to about 400 nanometers; an infrared light; and an ultraviolet light.

ABSTRACT

A contact lens is provided. One embodiment of the present invention provides a method for fitting and prescribing a contact lens. Another embodiment of the present invention comprises a contact lens construction that provides a stable prescription platform. Yet
5 another embodiment comprises a contact lens that is constructed to accommodate ectasia associated with keratoconus. This Abstract is provided for the sole purpose of complying with the Abstract requirement rules that allow a reader to quickly ascertain the subject matter of the disclosure contained herein. This Abstract is submitted with the explicit understanding that it will not be used to interpret or to limit the scope or the meaning of
10 the claims.






FIG. 4




FIG. 5





FIG. 6A

FIG. 6B




FIG. 7

COMBINED DECLARATION FOR PATENT APPLICATION AND POWER OF ATTORNEY

(Includes Reference to PCT International Applications)

ATTORNEY DOCKET NUMBER
30682-5

As a below named inventor, I (we) hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

CONTACT LENS

the specification of which (check only one item below):

☒ is attached hereto.☐ was filed as United States application

Serial No. _____

on _____

and was amended

on _____ (if applicable)

☐ was filed as PCT international application

Number _____

on _____

and was amended under PCT Article 19

on _____ (if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information that is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, §119 or §356 of any foreign application(s) for patent or inventor's certificate or of any PCT international application(s) designating at least one country other than the United States of America, listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed:

COUNTRY (if PCT, indicate "PCT")	APPLICATION NUMBER	DATE OF FILING (day, month, year)	PRIORITY CLAIMED UNDER 35 USC 119	
			<input type="checkbox"/> YES	<input type="checkbox"/> NO
			<input type="checkbox"/> YES	<input type="checkbox"/> NO
			<input type="checkbox"/> YES	<input type="checkbox"/> NO
			<input type="checkbox"/> YES	<input type="checkbox"/> NO
			<input type="checkbox"/> YES	<input type="checkbox"/> NO
			<input type="checkbox"/> YES	<input type="checkbox"/> NO

Combined Declaration For Patent Application and Power of Attorney (Continued) (Includes Reference to PCT International Applications)				ATTORNEY DOCKET NUMBER 30682-5	
I hereby claim the benefit under Title 35, United States Code §120 of any United States application(s) or PCT international application(s) designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in that/those prior application(s) in the manner provided by the first paragraph of Title 35, United States Code §112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations §1.56 which became available between the filing date of the prior application(s) and the national or PCT international filing date of this application:					
PRIOR U.S. APPLICATIONS OR PCT INTERNATIONAL APPLICATIONS DESIGNATING THE U.S. FOR BENEFIT UNDER 35 U.S.C. 120:					
U.S. APPLICATIONS				STATUS (Check one)	
U.S. APPLICATION NUMBER	U.S. FILING DATE		PATENTED	PENDING	ABANDONED
PCT APPLICATIONS DESIGNATING THE U.S.					
PCT APPLICATION NO.	PCT FILING DATE	U.S. SERIAL NUMBERS ASSIGNED (if any)			
POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith: PETER R. MARTINEZ, Reg. No. 42,845; MITCHELL P. BROOK, Reg. No. 32,967; PETER K. HAHN, Reg. No. 34,833; DAVID E. HEISEY, Reg. No. 42,651; and NICOLA A. PISANO, Reg. No. 34,408; all attorneys with the firm of LUCE, FORWARD, HAMILTON & SCRIPPS, which has an office address at 11978 El Camino Real, Suite 200, San Diego, CA 92130.					
Send Correspondence to: Peter R. Martinez, Esq. LUCE, FORWARD, HAMILTON & SCRIPPS 11988 El Camino Real, Suite 200 San Diego, California 92130				Direct Telephone Calls to: (name and telephone number) Peter R. Martinez (858) 720-6300	
2 0 1	FULL NAME OF INVENTOR	FAMILY NAME LEGERTON	FIRST GIVEN NAME Jerome	SECOND GIVEN NAME	
	RESIDENCE & CITIZENSHIP	CITY San Diego	STATE OR FOREIGN COUNTRY California	COUNTRY OF CITIZENSHIP USA	
	POST OFFICE ADDRESS	POST OFFICE ADDRESS 874 Harbor View Place	CITY San Diego	STATE & ZIP CODE/COUNTRY California 92106	
2 0 2	FULL NAME OF INVENTOR	FAMILY NAME Chen	FIRST GIVEN NAME Barry	SECOND GIVEN NAME	
	RESIDENCE & CITIZENSHIP	CITY San Diego	STATE OR FOREIGN COUNTRY CA	COUNTRY OF CITIZENSHIP USA	
	POST OFFICE ADDRESS	POST OFFICE ADDRESS 8578 Burr Lane	CITY San Diego	STATE & ZIP CODE/COUNTRY California 92129	
<input type="checkbox"/> Additional inventors are being named on the ____ supplemental Additional Inventor(s) sheets(s) attached hereto.					
I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.					
SIGNATURE OF INVENTOR 201			SIGNATURE OF INVENTOR 202		
DATE 11-14-03			DATE		

Combined Declaration For Patent Application and Power of Attorney (Continued) (Includes Reference to PCT International Applications)			ATTORNEY DOCKET NUMBER 30682-5	
I hereby claim the benefit under Title 35, United States Code §120 of any United States application(s) or PCT international application(s) designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in that/those prior application(s) in the manner provided by the first paragraph of Title 35, United States Code §112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations §1.56 which became available between the filing date of the prior application(s) and the national or PCT international filing date of this application:				
PRIOR U.S. APPLICATIONS OR PCT INTERNATIONAL APPLICATIONS DESIGNATING THE U.S. FOR BENEFIT UNDER 35 U.S.C. 120:				
U.S. APPLICATIONS			STATUS (Check one)	
U.S. APPLICATION NUMBER	U.S. FILING DATE	PATENTED	PENDING	ABANDONED
PCT APPLICATIONS DESIGNATING THE U.S.				
PCT APPLICATION NO.	PCT FILING DATE	U.S. SERIAL NUMBERS ASSIGNED (if any)		
POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith: PETER R. MARTINEZ, Reg. No. 42,845; MITCHELL P. BROOK, Reg. No. 31,967; PETER K. HAHN, Reg. No. 34,833; DAVID E. HEISEY, Reg. No. 42,651; and NICOLA A. PISANO, Reg. No. 34,408; all attorneys with the firm of LUCE, FORWARD, HAMILTON & SCRIPPS, which has an office address at 11978 El Camino Real, Suite 200, San Diego, CA 92130.				
Send Correspondence to: Peter R. Martinez, Esq. LUCE, FORWARD, HAMILTON & SCRIPPS 11988 El Camino Real, Suite 200 San Diego, California 92130			Direct Telephone Calls to: <i>(name and telephone number)</i> Peter R. Martinez (858) 720-6300	
2 0 1	FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
	RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
	POST OFFICE ADDRESS	CITY	STATE & ZIP CODE/COUNTRY	
		LEGERTON	Jerome	
		San Diego	California	USA
		874 Harbor View Place	San Diego	California 92106
2 0 2	FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
	RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
	POST OFFICE ADDRESS	CITY	STATE & ZIP CODE/COUNTRY	
		Chen	Barry	
		San Diego	CA	USA
		8578 Burr Lane	San Diego	California 92129
<input type="checkbox"/> Additional inventors are being named on the ____ supplemental Additional Inventor(s) sheet(s) attached hereto.				
I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.				
SIGNATURE OF INVENTOR 201			SIGNATURE OF INVENTOR 202	
DATE			DATE	
			11/14/03	

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/US04/036649

International filing date: 03 November 2004 (03.11.2004)

Document type: Certified copy of priority document

Document details: Country/Office: US
Number: 10/713,874
Filing date: 14 November 2003 (14.11.2003)

Date of receipt at the International Bureau: 23 December 2004 (23.12.2004)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse